

# **SCTE** | **STANDARDS**

---

**Digital Video Subcommittee**

---

**AMERICAN NATIONAL STANDARD**

**ANSI/SCTE 243-1 2022**

**Next Generation Audio Carriage Constraints for Cable  
Systems: Part 1 – Common Transport Signaling**

## NOTICE

The Society of Cable Telecommunications Engineers (SCTE) Standards and Operational Practices (hereafter called “documents”) are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interoperability, interchangeability, best practices, and the long term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE members.

SCTE assumes no obligations or liability whatsoever to any party who may adopt the documents. Such adopting party assumes all risks associated with adoption of these documents and accepts full responsibility for any damage and/or claims arising from the adoption of such documents.

NOTE: The user’s attention is called to the possibility that compliance with this document may require the use of an invention covered by patent rights. By publication of this document, no position is taken with respect to the validity of any such claim(s) or of any patent rights in connection therewith. If a patent holder has filed a statement of willingness to grant a license under these rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such a license, then details may be obtained from the standards developer. SCTE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this document have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE web site at <https://scte.org>.

All Rights Reserved  
©2022 Society of Cable Telecommunications Engineers, Inc.  
140 Philips Road  
Exton, PA 19341

## Document Types and Tags

Document Type: Specification

Document Tags:

- |  |                                    |  |
|--|------------------------------------|--|
| <input type="checkbox"/> Test or Measurement                     | <input type="checkbox"/> Checklist | <input checked="" type="checkbox"/> Facility |
| <input type="checkbox"/> Architecture or Framework               | <input type="checkbox"/> Metric    | <input type="checkbox"/> Access Network      |
| <input checked="" type="checkbox"/> Procedure, Process or Method | <input type="checkbox"/> Cloud     | <input type="checkbox"/> Customer Premises   |

## Document Release History

Release	Date
SCTE 243-1 2017	10/10/2017
SCTE 243-1 2022	October 2022

Note: Standards that are released multiple times in the same year use: a, b, c, etc. to indicate normative balloted updates and/or r1, r2, r3, etc. to indicate editorial changes to a released document after the year.

# Table of Contents

Title	Page Number
NOTICE.....	2
Document Types and Tags.....	3
Document Release History.....	3
Table of Contents.....	4
1. Introduction.....	6
1.1. Executive Summary.....	6
1.2. Scope.....	6
1.3. Benefits.....	6
2. Normative References.....	6
2.1. SCTE References.....	6
2.2. Standards from Other Organizations.....	6
2.3. Other Published Materials.....	7
3. Informative References.....	7
3.1. SCTE References.....	7
3.2. Standards from Other Organizations.....	7
3.3. Other Published Materials.....	7
4. Compliance Notation.....	8
5. Abbreviations and Definitions.....	8
5.1. Abbreviations.....	8
5.2. Definitions.....	8
6. Introduction.....	9
6.1. Audio Preselection Information.....	9
6.2. Carriage of NGA.....	10
6.3. Audio Specific Capabilities.....	10
7. Signaling of NGA codecs in MPEG-2 TS.....	10
7.1. Audio Preselection Information.....	10
7.1.1. audio_preselection_descriptor.....	10
7.1.2. Usage of the audio_preselection_descriptor.....	11
7.2. Emergency Information.....	12
7.2.1. Introduction.....	12
7.2.2. emergency_information_descriptor.....	12
7.3. Accessibility Information.....	14
7.4. Example of descriptors usage in PMT.....	15
8. Signaling of NGA codecs in MPEG DASH.....	15
8.1. Background and Basic Use Cases.....	16
8.2. Assumptions and Definitions.....	16
8.3. Codec-Independent Mapping to DASH.....	16
8.4. Codec-specific Properties.....	16

## List of Figures

Title	Page Number
Figure 1 - Example Broadcast Audio Preselections in an Audio Program.....	12

## List of Tables

<b>Title</b>	<b>Page Number</b>
Table 1 - Bit Stream Syntax for emergency information descriptor .....	13
Table 2 - Mapping of accesibility fields to Audio Accesibility Services .....	14
Table 3 - Possible usage in PMT SI tables of descriptors for single-stream delivery.....	15
Table 4 - Possible usage in PMT SI tables of descriptors for main stream .....	15
Table 5 - Possible usage in PMT SI tables of descriptors for auxiliary streams.....	15

## 1. Introduction

### 1.1. Executive Summary

This standard is part of a suite documenting carriage constraints of Next Generation Audio (NGA) codecs in MPEG-2 transport systems and in MPEG DASH. It is intended to be used in conjunction with the specific audio technologies described in subsequent Parts of this standard (see [SCTE 243-2], [SCTE 243-3], and [SCTE 243-4]).

### 1.2. Scope

This document specifies the common framework for carriage constraints of Next Generation Audio (NGA) codecs in MPEG-2 transport systems and in MPEG DASH. It is intended to be used in conjunction with the specific audio technologies described in subsequent Parts of this standard.

The common descriptors necessary to signal NGA in MPEG-2 transport systems are defined in [ISO 13818-1] and ETSI [EN 300-468], and their usage is described in this Part of the standard. Additional codec specific descriptors are defined in subsequent Parts (which defines codec specific carriage constraints: . see ([SCTE 243-2], [SCTE 243-3], and [SCTE 243-4]).

Multiplexing and transport for cable using MPEG-2 transport systems are defined in [SCTE 54] . This standard provides a general description of NGA systems) and subsequent Parts of the standard define codec specific carriage constraints) (see [SCTE 243-2], [SCTE 243-3], and [SCTE 243-4]).

### 1.3. Benefits

The Next Generation Audio (NGA) system audio system provides immersive and personalizable sound for television. It is not compatible with the audio system used in [SCTE 54] -era service.

## 2. Normative References

The following documents contain provisions which, through reference in this text, constitute provisions of this document. The editions indicated were valid at the time of subcommittee approval. All documents are subject to revision and, while parties to any agreement based on this document are encouraged to investigate the possibility of applying the most recent editions of the documents listed below, they are reminded that newer editions of those documents might not be compatible with the referenced version.

### 2.1. SCTE References

No normative references are applicable.

### 2.2. Standards from Other Organizations

- |               |   |
|---------------|---|
| [A342-1]      | ATSC A/342:2021 Part 1: Audio Common Elements   |
| [ISO 13818-1] | ISO/IEC 13818-1:2015, Information technology – Generic coding of moving pictures and associated audio information: Systems                  |
| [EN 300-468]  | ETSI EN 300 468 v1.16.1 (2019-08), Digital Video Broadcasting (DVB); Specification for Service Information (SI) in DVB systems (EN 300 468) |

- [IOP] DASH IF: “Guidelines for Implementation: DASH-IF Interoperability Points for ATSC 3.0, Version 1.0,” DASH Interoperability Forum, January 31, 2016.  
<http://dashif.org/wp-content/uploads/2017/02/DASH-IF-IOP-for-ATSC3-0-v1.0.pdf>

### 2.3. Other Published Materials

No normative references are applicable.

## 3. Informative References

The following documents might provide valuable information to the reader but are not required when complying with this document.

### 3.1. SCTE References

- [SCTE 54] SCTE 54 2020, Digital Video Service Multiplex and Transport System Standard for Cable Television
- [SCTE 242-1] SCTE 242-1 202x, Next Generation Audio Coding Constraints for Cable Systems: Part 1 – Introduction and Common Constraints
- [SCTE 243-2] SCTE 243-2 202x, Next Generation Audio Carriage Constraints For Cable Systems: Part 2 – AC-4 Audio Carriage Constraints
- [SCTE 243-3] SCTE 243-3 202x, Next Generation Audio Carriage Constraints for Cable Systems: Part 3 –MPEG-H Audio Carriage Constraints
- [SCTE 243-4] SCTE 243-4 202x, Next Generation Audio Carriage Constraints for Cable Systems: Part 4 –DTS-UHD Audio Carriage Constraints

### 3.2. Standards from Other Organizations

- [A331] ATSC A/331:202x, Signaling, Delivery, Synchronization and Error Protection
- [ISO 23009-1] ISO/IEC 23009-1:2014/Amd 4:2017 Segment Independent SAP Signalling (SISSI), MPD chaining, MPD reset and other extensions

### 3.3. Other Published Materials

No informative references are applicable.

## 4. Compliance Notation

<i>shall</i>	This word or the adjective “ <i>required</i> ” means that the item is an absolute requirement of this document.
<i>shall not</i>	This phrase means that the item is an absolute prohibition of this document.
<i>forbidden</i>	This word means the value specified <i>shall</i> never be used.
<i>should</i>	This word or the adjective “ <i>recommended</i> ” means that there <i>may</i> exist valid reasons in particular circumstances to ignore this item, but the full implications <i>should</i> be understood and the case carefully weighed before choosing a different course.
<i>should not</i>	This phrase means that there <i>may</i> exist valid reasons in particular circumstances when the listed behavior is acceptable or even useful, but the full implications <i>should</i> be understood and the case carefully weighed before implementing any behavior described with this label.
<i>may</i>	This word or the adjective “ <i>optional</i> ” indicate a course of action permissible within the limits of the document.
deprecated	Use is permissible for legacy purposes only. Deprecated features <i>may</i> be removed from future versions of this document. Implementations <i>should</i> avoid use of deprecated features.

## 5. Abbreviations and Definitions

### 5.1. Abbreviations

AD	Audio Description
DE	Dialog Enhancement
EINFO	Emergency Information
NGA	Next Generation Audio
PES	Packetized Elementary Stream
PMT	Program Map Table
PSI	Program Specific Information
TS	Transport Stream
VDS	Video Description Service <sup>1</sup>

### 5.2. Definitions

This document uses the terminology specific to the ATSC 3.0 audio system as defined in ATSC [A342-1] Clause 4. Additionally, the following definitions are used:

Audio Description	Defined in a regulation of the United States, 47 CFR §79.3(a)(3), as “The insertion of audio narrated descriptions of a television program’s key visual elements into natural pauses between the program’s dialogue.” It has sometimes been termed Video Description or VDS. Such usage is considered obsolete.
-------------------	---

---

<sup>1</sup> As Defined in a regulation of the United States, 47 CFR §79.3(a)(3), as “The insertion of audio narrated descriptions of a television program’s key visual elements into natural pauses between the program’s dialogue.” It has sometimes been termed Video Description or VDS. Such usage is considered obsolete.

Audio Preselection	set of Audio Program Components representing a version of the Audio Program that may be selected by a user for simultaneous decoding. An Audio Preselection is a sub-selection from all available Audio Program Components of one Audio Program. An Audio Preselection can be considered the NGA equivalent of audio services in predecessor systems, whereby each audio service comprises a complete audio mix.
auxiliary NGA stream	NGA stream delivered using NGA multi-stream delivery, and containing additional Audio Program Components not contained in the main NGA stream.
main NGA stream	NGA stream delivered using NGA multi-stream delivery, and containing at least all the Audio Program Components corresponding to at least one Audio Preselection.
multi-stream delivery	method for carrying Audio Program Components in several NGA streams (e.g., when Audio Program Components offering additional languages are carried in separate elementary streams to facilitate re-multiplexing or service aggregation).
NGA stream	audio elementary stream containing one or more Audio Program Components of one Audio Program.
single-stream delivery	method for carrying all Audio Program Components in a single NGA stream.

## 6. Introduction

Next Generation Audio (NGA) systems provide Broadcasters, Operators and Content Providers with more flexibility to create and deliver their content. These NGA systems introduce a number of new concepts and techniques, including:

- The capability to provide Immersive Audio with the addition of height elements,
- The capability to provide personalization options to broadcasters and consumers,
- The introduction of Audio Objects to facilitate immersive and personalized audio.

### 6.1. Audio Preselection Information

Audio Preselections are used for offering alternative audio mixes to the user for “User Personalization”. These mixes could include existing service types such as alternative language versions or Audio Description (AD), but could also include new services such as “home and away” commentary mix for a sports event or a team channel.

NGA systems enable user control of certain aspects of the Audio Scene (e.g., adjusting the relative level of dialogue with respect to the ambient music and effects) by combining the Audio Program Components, present in one or more NGA streams, at the receiver side. In this way several Audio Program Components can be shared between different Audio Preselections, allowing for very efficient delivery of additional services compared to legacy systems (e.g., the multi-language functionality can be achieved using supplementary streams in legacy systems). This is a major advantage of the NGA systems, where one stream contains much more than one complete audio main.

## 6.2. Carriage of NGA

Audio Program Components corresponding to one or more Audio Preselections can be delivered in a single elementary stream (i.e., NGA single-stream delivery) or in multiple elementary streams (i.e., NGA multi-stream delivery).

In case of single-stream delivery all Audio Program Components of one Audio Program are carried in a single NGA stream, together with the signaling information of the available Audio Preselections.

In case of multi-stream delivery the Audio Program Components of one Audio Program are not carried within one single NGA stream, but in two or more NGA streams. In this case the main NGA stream contains at least all the Audio Program Components corresponding to one Audio Preselection. The auxiliary streams may contain additional Audio Program Components (e.g., additional language tracks).

The metadata formats embedded in the NGA streams shall be used only for carrying audio related data.

## 6.3. Audio Specific Capabilities

Typical differentiation of receiver capabilities for the audio decoding and rendering pipeline may use one or multiple of the following properties:

- Codec capabilities:
- Codec, Profile and Level
- Rendering capabilities/environment
- User preferences and settings (accessibility, language, role)
- User interaction and Personalization

# 7. Signaling of NGA codecs in MPEG-2 TS

## 7.1. Audio Preselection Information

For signaling the features of NGA systems in MPEG-2 Transport Streams the concept of Audio Preselection is used as defined in ETSI [EN 300-468] subclause 6.4.

### 7.1.1. *audio\_preselection\_descriptor*

The **audio\_preselection\_descriptor** provides information about the available Audio Preselections for one Audio Program contained in one or more NGA associated elementary streams within a transport stream that are to be identified in the PSI PMT sections.

The descriptor may be used by the receiver for selection of the appropriate Audio Preselection to present the Audio Program to the user, and to locate the constituent elementary streams. The **audio\_preselection\_descriptor** is defined in ETSI [EN 300-468] subclause 6.4 and is located in the PMT of the PSI Tables defined in ETSI [EN 300-468].

The **audio\_preselection\_descriptor**, when present, shall be used as specified in ETSI [EN 300-468] subclause 6.4 and shall be included in the program map section at most once in the ES\_info descriptor loop that describes the elementary stream carrying the main NGA stream.

The **audio\_preselection\_descriptor** shall be present for all NGA elementary streams that contain Audio Preselections for the Audio Program.

In case of single-stream delivery, the use of the **audio\_preselection\_descriptor** is optional.

In case of multi-stream delivery, the following rules apply:

- the **audio\_preselection\_descriptor** shall be included in the program map section at most once in the ES\_info descriptor loop that describes the elementary stream carrying the main NGA stream.
- the **stream\_identifier\_descriptor** (defined in ETSI [EN 300-468] subclause 6.2) shall be included in the program map section in each relevant ES\_info descriptor loop that describes an elementary stream carrying an additional NGA stream.

When the **audio\_preselection\_descriptor** is included in the program map section, the **ISO\_639\_Language\_descriptor** ([ISO 13818-1] subclause 2.6.18) shall not be included in the program map section in any relevant ES\_info descriptor loop that describes an elementary stream carrying the main or an auxiliary NGA stream.

### ***7.1.2. Usage of the audio\_preselection\_descriptor***

The **audio\_preselection\_descriptor** is used for signaling the NGA features that the receiver may use for selection of the appropriate Audio Preselection and NGA streams to present the Audio Program to the user. For each available Audio Preselection, the descriptor provides information about the available accessibility features and languages, indication about the preferred reproduction layout and the interactivity options.

Figure 1 illustrates an example of one Audio Program containing several available Audio Preselections, assuming all Audio Program Components and the Audio Preselection information are contained in the same stream (single-stream delivery case).

Audio Preselection Descriptor	NGA Elementary Stream					
	Audio Program Components					
	M&E	Dialogue EN	Dialogue ES	AD EN	AD ES	Team Radio
Default Preselection (English)	M&E	Dialogue EN	Dialogue ES	AD EN	AD ES	Team Radio
English Video Description Preselection	M&E	Dialogue EN	Dialogue ES	AD EN	AD ES	Team Radio
Spanish Preselection	M&E	Dialogue EN	Dialogue ES	AD EN	AD ES	Team Radio
Spanish Video Description Preselection	M&E	Dialogue EN	Dialogue ES	AD EN	AD ES	Team Radio
English Team Radio Preselection	M&E	Dialogue EN	Dialogue ES	AD EN	AD ES	Team Radio
M&E Only Preselection	M&E	Dialogue EN	Dialogue ES	AD EN	AD ES	Team Radio

Figure 1 - Example Broadcast Audio Preselections in an Audio Program

## 7.2. Emergency Information

### 7.2.1. Introduction

The ATSC 3.0 Emergency Alert System structure, defined in ATSC [A331] Annex G, specifies several types of emergency information that can be delivered to TV receivers including audio/aural representation of the emergency information. This section provides appropriate signaling of the audio/aural representation of the emergency information for MPEG-2 transport systems.

### 7.2.2. *emergency\_information\_descriptor*

The **emergency\_information\_descriptor** provides information about the available audio/aural representation of the emergency information contained in one or more NGA associated elementary streams within a transport stream that are to be identified in the PSI PMT sections.

The descriptor shall be present if at least one of the Audio Preselections, available in the **audio\_preselection\_descriptor**, contains an audio/aural representation of the emergency information.

The **emergency\_information\_descriptor** shall be included in the program map section at most once in the ES\_info descriptor loop that describes the elementary stream carrying the main NGA stream that is included in a transport stream.

**Table 1 - Bit Stream Syntax for emergency information descriptor**

Syntax	No. of Bits	Format
emergency_information_descriptor() {		
<b>descriptor_tag</b>	8	uimsbf
<b>descriptor_length</b>	8	uimsbf
<b>num_preselections</b>	5	uimsbf
<b>audio_representation_emergency</b>	1	uimsbf
<b>reserved</b>	2	'11'
for (i=0; i<num_preselections; i++) {		
<b>preselection_id</b>	5	uimsbf
<b>reserved</b>	3	'1 1111'
}		
<b>emergency_information_start_time_present</b>	1	bslbf
<b>emergency_information_end_time_present</b>	1	bslbf
<b>reserved</b>	6	'11 1111'
If (emergency_information_start_time_present) {		
<b>emergency_information_start_time</b>	32	uimsbf
<b>reserved</b>	6	'11 1111'
<b>emergency_information_start_time_ms</b>	10	uimsbf
}		
If (emergency_information_end_time_present) {		
<b>emergency_information_end_time</b>	32	uimsbf
<b>reserved</b>	6	'11 1111'
<b>emergency_information_end_time_ms</b>	10	uimsbf
}		
}		

**descriptor\_tag:** The descriptor tag shall be set to 0xED to identify the descriptor as an **emergency\_information\_descriptor**.

**descriptor\_length:** This 8-bit field shall specify the number of bytes of the descriptor immediately following the **descriptor\_length** field.

**num\_preselections:** This 5-bit unsigned integer field shall specify the number of Audio Preselections for which the emergency information described in this descriptor is valid. The minimum number of **num\_preselections** shall be "1".

**audio\_representation\_emergency:** This 1-bit Boolean field shall indicate, when set to '1', that the Audio Preselection contains aural/audio representation of emergency information.

**preselection\_id:** This 5-bit unsigned integer field identifies each Audio Preselection for which the emergency information described in this descriptor is valid.

**emergency\_information\_start\_time\_present:** This 1-bit Boolean flag shall indicate, when set to '1', that the fields **emergency\_information\_start\_time** and **emergency\_information\_start\_time\_ms** are present. When set to '0', the fields **emergency\_information\_start\_time** and **emergency\_information\_start\_time\_ms** shall not be present and the start time of the aural/audio representation of the emergency information shall be inferred to be equal to the presentation time of first media sample in presentation order in the audio asset.

**emergency\_information\_end\_time\_present:** This 1-bit Boolean flag shall indicate, when set to ‘1’, that the fields **emergency\_information\_end\_time** and **emergency\_information\_end\_time\_ms** are present. When set to ‘0’, the fields **emergency\_information\_end\_time** and **emergency\_information\_end\_time\_ms** shall not be present and the end time of the aural/audio representation of the emergency information shall be inferred to be equal to the presentation time of the last media sample in presentation order in the audio asset.

**emergency\_information\_start\_time:** This 32-bit unsigned integer shall indicate the start time of the aural/audio representation of the emergency information, as the least-significant 32 bits of the count of the number of seconds since January 1, 1970 00:00:00, International Atomic Time (TAI).

**emergency\_information\_start\_time\_ms:** This 10-bit unsigned integer in the range 0 to 999 shall indicate the milliseconds offset from the time indicated in **emergency\_information\_start\_time**, such that the formula:

$$\text{emergency\_information\_start\_time} + (\text{emergency\_information\_start\_time\_ms}/1000)$$

yields the start time of the audio/aural emergency information to the nearest 1 millisecond.

**emergency\_information\_end\_time:** This 32-bit unsigned integer shall indicate the end time of the aural/audio representation of the emergency information, as the least-significant 32 bits of the count of the number of seconds since January 1, 1970 00:00:00, International Atomic Time (TAI).

**emergency\_information\_end\_time\_ms:** This 10-bit unsigned integer in the range 0 to 999 shall indicate the milliseconds offset from the time indicated in **emergency\_information\_end\_time**, such that the formula:

$$\text{emergency\_information\_end\_time} + (\text{emergency\_information\_end\_time\_ms}/1000)$$

yields the end time of the audio/aural emergency information to the nearest 1 millisecond.

### 7.3. Accessibility Information

The accessibility support is signaled for each Audio Preselection. The accessibility fields are defined in the **audio\_preselection\_descriptor** and in the **emergency\_information\_descriptor**. Table 2 specifies the mapping of the accessibility fields to the ATSC 3.0 audio accessibility services.

**Table 2 - Mapping of accesibility fields to Audio Accesibility Services**

Accessibility fields	Location	Audio Accessibility Service
<b>audio_description</b>	<b>audio_preselection_descriptor</b>	Audio Description (AD) for Visually Impaired
<b>dialogue_enhancement</b>	<b>audio_preselection_descriptor</b>	Dialog Enhancement (DE) enabled
<b>audio_representation_emergency</b>	<b>emergency_information_descriptor</b>	Audio/Aural representation of Emergency Information (EINFO)

Audio Description Service for Visually Impaired – indicates, when **audio\_description** field is set to "1", the presence of the audio accessibility service for visually impaired for the Audio Preselection.

Dialog Enhancement enabled – indicates, when **dialogue\_enhancement** field is set to "1", that the Audio Preselection enables the ability for a receiver to change the relative level of dialog to enhance dialog intelligibility.

Audio/Aural representation of Emergency Information – indicates, when **audio\_representation\_emergency** field is set to "1", that the Audio Preselection contains aural/audio representation of emergency information.

#### 7.4. Example of descriptors usage in PMT

Table 3 specifies an example of how the descriptors declared or defined within the present document, can be used in the PSI PMT depending on the NGA features available in a single NGA stream. This does not imply that their use in other ways is restricted.

**Table 3 - Possible usage in PMT SI tables of descriptors for single-stream delivery**

Descriptor	Stereo	EINFO	Multi-lang.	DE EI	AD
<b>codec specific descriptors</b>	<b>M</b>	<b>M</b>	<b>M</b>	<b>M</b>	<b>M</b>
<b>audio_preselection_descriptor</b>	<b>O</b>	<b>O</b>	<b>M</b>	<b>M</b>	<b>M</b>
<b>emergency_information_descriptor</b>	<b>O</b>	<b>M</b>	<b>O</b>	<b>M</b>	<b>O</b>
<b>stream_identifier_descriptor</b>	<b>O</b>	<b>O</b>	<b>O</b>	<b>O</b>	<b>O</b>
M = mandatory in PMT; O = optional in PMT; X = Not Allowed					

Table 4 and Table 5 specify a similar example of how the descriptors declared or defined within the present document, can be used in the PSI PMT depending on the NGA features available in the case of NGA multi-stream delivery. This does not imply that their use in other ways is restricted.

**Table 4 - Possible usage in PMT SI tables of descriptors for main stream**

Descriptor	Stereo	EINFO	Multi-lang.	DE EI	AD
<b>codec specific descriptors</b>	<b>M</b>	<b>M</b>	<b>M</b>	<b>M</b>	<b>M</b>
<b>audio_preselection_descriptor</b>	<b>O</b>	<b>M</b>	<b>M</b>	<b>M</b>	<b>M</b>
<b>emergency_information_descriptor</b>	<b>O</b>	<b>M</b>	<b>O</b>	<b>M</b>	<b>O</b>
<b>stream_identifier_descriptor</b>	<b>O</b>	<b>O</b>	<b>O</b>	<b>O</b>	<b>O</b>
M = mandatory in PMT; O = optional in PMT; X = Not Allowed					

**Table 5 - Possible usage in PMT SI tables of descriptors for auxiliary streams**

Descriptor	Stereo	EINFO	Multi-lang.	DE EI	AD
<b>codec specific descriptors</b>	N/A	<b>O</b>	<b>O</b>	<b>O</b>	<b>O</b>
<b>audio_preselection_descriptor</b>	N/A	X	X	X	X
<b>emergency_information_descriptor</b>	N/A	X	X	X	X
<b>stream_identifier_descriptor</b>	N/A	<b>M</b>	<b>M</b>	<b>M</b>	<b>M</b>
M = mandatory in PMT; O = optional in PMT; X = Not Allowed					

## 8. Signaling of NGA codecs in MPEG DASH

For signaling audio, the Preselection feature defined in [ISO 23009-1] is used. It is specifically adapted to address the Next Generation Audio concepts (see [A342-1]).

### **8.1. Background and Basic Use Cases**

The use cases specified in DASH-IF [IOP] subclause 5.4.1 are expected to be supported by the client reference model.

### **8.2. Assumptions and Definitions**

The assumptions and definitions specified in DASH-IF IOP subclause 5.4.2 shall apply.

### **8.3. Codec-Independent Mapping to DASH**

The attributes available in Adaptation Sets and Media Content Components specified in DASH-IF IOP subclause 5.4.3 shall be used.

### **8.4. Codec-specific Properties**

The codec-specific properties on how codecs can be mapped on the generic data structure defined in Clause 8.3 are specified in subsequent Parts of this standard. This typically includes for each codec:

- Codecs parameter settings
- Usage of the Preselection elements
- Random Access Point and Switching Point requirements
- The definition of bitstream switching or media level switching
- File format encapsulation requirements