

# SCTE · ISBE<sup>®</sup>

## S T A N D A R D S

---

**ENGINEERING COMMITTEE**  
**Network Operations Subcommittee**

---

**AMERICAN NATIONAL STANDARD**

**ANSI/SCTE 110 2020**

**Hybrid Fiber Coax Outside Plant Status Monitoring:  
Alternative Power Supply to Transponder Interface Bus  
(PSTIB) For HMS Transponders**

## NOTICE

The Society of Cable Telecommunications Engineers (SCTE) / International Society of Broadband Experts (ISBE) Standards and Operational Practices (hereafter called “documents”) are intended to serve the public interest by providing specifications, test methods and procedures that promote uniformity of product, interchangeability, best practices and ultimately the long-term reliability of broadband communications facilities. These documents shall not in any way preclude any member or non-member of SCTE•ISBE from manufacturing or selling products not conforming to such documents, nor shall the existence of such standards preclude their voluntary use by those other than SCTE•ISBE members.

SCTE•ISBE assumes no obligations or liability whatsoever to any party who may adopt the documents. Such adopting party assumes all risks associated with adoption of these documents, and accepts full responsibility for any damage and/or claims arising from the adoption of such documents.

Attention is called to the possibility that implementation of this document may require the use of subject matter covered by patent rights. By publication of this document, no position is taken with respect to the existence or validity of any patent rights in connection therewith. SCTE•ISBE shall not be responsible for identifying patents for which a license may be required or for conducting inquiries into the legal validity or scope of those patents that are brought to its attention.

Patent holders who believe that they hold patents which are essential to the implementation of this document have been requested to provide information about those patents and any related licensing terms and conditions. Any such declarations made before or after publication of this document are available on the SCTE•ISBE web site at <http://www.scte.org>.

All Rights Reserved  
© Society of Cable Telecommunications Engineers, Inc. 2020  
140 Philips Road  
Exton, PA 19341

## TABLE OF CONTENTS

<b>1</b>	<b>INTRODUCTION .....</b>	<b>4</b>
<b>2</b>	<b>INCLUSION BY REFERENCE .....</b>	<b>4</b>
2.1	SECTION 3.1.3 OF ANSI/SCTE 25-3 .....	4
2.2	SECTION 3.1.4 OF ANSI/SCTE 25-3 .....	4

## LIST OF TABLES

Table 1: RJ-45 Connector Pin Assignment

## 1 Introduction

This document is identical to SCTE 110 2011 except for informative components which may have been updated such as the title page, NOTICE text, headers and footers. No normative changes have been made to this document.

The Power Supply to Transponder Interface Bus (PSTIB) was defined by ANSI/SCTE 25-3. Some applications have been identified that may have under certain conditions a powering requirement which exceeds those defined by HMS 022. This specification will not delete or replace the ANSI/SCTE 25-3 specification but will be a supplement to and will coexist with that document

## 2 Inclusion by Reference

This document incorporates by reference, all requirements of ANSI/SCTE 25-3 except Sections 3.1.3 and 3.1.4 which are replaced by those in this section.

### 2.1 Section 3.1.3 of ANSI/SCTE 25-3

Section 3.1.4 of ANSI/SCTE 25-3 shall be replaced by the following in its entirety:

#### 3.1.3 Connector Signals

Connector pins shall support signaling as described in Table 1.

**Table 1: RJ-45 Connector Pin Assignment**

Connected Pin Number	Signal
1, 8	Ground
2, 7	+24 VDC $\pm$ 15% at 4.8 watts
3, 6	RS-485 (+)
4, 5	RS-485 (-)

### 2.2 Section 3.1.4 of ANSI/SCTE 25-3

Section 3.1.4 of ANSI/SCTE 25-3 shall be replaced by the following in its entirety.

#### 3.1.4 Transponder Power

1. The power supply shall implement appropriate isolation and system grounding such that the communication interface and transponder power remains functional under the operating conditions defined herein.

2. The transponder shall be bonded to chassis ground directly and/or through the system coaxial cable sheath.
3. Optionally, transponder power may be bonded to chassis ground at the power supply interface. The power supply vendor shall determine this.
4. The power supply shall implement appropriate over-current and short-circuit protection of transponder power such that the communication interface and transponder power remain functional under the operating conditions defined herein.
5. Up to eight (8) power supplies may be connected in parallel using the RS-485 interface.
6. Under the operating requirements defined herein, the Power Supply shall be able to supply 4.8 watts of continuous power to the PSTIB.
7. Under the operating requirements defined herein, the Transponder shall draw no more than 4.8 watts of power from the PSTIB.
8. During startup, while the power supply is coming up to the minimum voltage requirement, the transponder shall limit inrush current to no more than 250mA. and power draw to no more than 4.8 watts.
9. During startup the Power Supply shall achieve the minimum voltage requirement within 1 second.